



WL250 Features

- Filtered chilled and hot water
- UV technology to reduce bacterial growth
- Tower and countertop models
- Easy connection to your existing water supply
- Option for drip tray drainage



Tested and Certified



CE QUALITY & SAFETY GUARANTEED

Waterlogic International Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo are registered trademarks in countries where the Group operates. Waterlogic International Limited is licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Speak to a Water Expert

See business card for local distributor or visit www.waterlogiccanada.com

Tel 1.800.277.2249

Water Options	Technical Features		
 Cold water  Hot water	Type available	Tower Countertop	
	Tower dimensions	13.75" (W) x 41" (H) x 14.5" (D)	
	Counter top dimensions	13.75" (W) x 17.75" (H) x 14.5" (D)	
	Compressor	120V/60Hz	
	Dispense area height	8.5in	
	Weight	Tower: 58 lbs Counter Top: 42 lbs	
	Recommended filtration	Countertop: Carbon Block (CBC) 1 micron with lead and cyst reduction Tower: Sediment Block, Carbon Block (CBC), Granular Activated Carbon (GAC)	
	Additional features	Mode Indicator Leak Detection *CT only	
	Capacity	Hot tank: 1.5 liters	Cold tank: 4 liters tower 2 liters counter top
	Water temperatures	Cold: 40°F Hot: 188°F	

02-091401

Visit us at www.waterlogic.us